


## ROOM KIOSK - CONFERENCE ROOM SCHEDULING DISPLAY



**Meeting Machines are optimized for stability and long-term use.  
The RFID reader provides security and easy check in.**

## Features



- ✓ Designed to run AgilQuest Forum
- ✓ 11.6" and 15.6" sizes with thin and attractive aluminum frames
- ✓ TAA Compliant and PIV Card enabled
- ✓ Power Over Ethernet (PoE + IEEE802.at / 30w minimum)
- ✓ RGB LED Indicator Lights on the front of the display
- ✓ PCAP Touch Screen
- ✓ 125KHz and 13.56MHz antennas, and HID RFID Reader using Elatec Nano technology
- ✓ High-end design with protective hardened glass front that is durable and easy to clean
- ✓ Three USB 3.0 ports on the back (hidden) + one USB 2.0 externally accessible (see below)
- ✓ Standard 75 x 75 VESA pattern and single and dual gang box mounting holes



The following table shows model specific data for our “standard” Meeting Machines products, custom color, logo printing, configuration, and factory provisioning is available. Full customization and other sizes are available upon special request, we will work with you as a project to define your specific needs.

## MEETING MACHINES DOOR SIGNS CPU

OS	Windows 7, 8.1, and 10, Linux 16.04	Display panel	16:9 LCD with LED backlight
CPU	Intel® Braswell® processor N3160	Touch technology	Projective Capacitive Touch (PCAP)
RFID	Elatec Nano 125KHz and 13.56MHz	Video ports	HDMI Output
Full Size Mini-PCIe	1	Internal audio	HD Audio CODEC
POE+	Integrated	External ports	2 x USB 3.0 & 1 x USB 2.0
Internal Storage	4GB DDR3 / 64GB mSATA	Network	GbE LAN

## 11.6” DISPLAY

## MM116

Size diagonal (Inches)	11.6"	Unit size WxH (mm)	12.36" x 7.76"
Active Area WxH (inches)	10.07 x 5.67	Surface Treatment	Anti-Glare, 3H
Resolution (pixels)	1366x768	Shipping size WxHxD (inches)	16 x 12 x 2.5 (in box)
Viewing angle L/R/D/U	85/85/85/85	Shipping weight (Lbs)	6.75 (in box)
Brightness (cd/m2)	320	Mounting pattern (mm)	75x75
Contrast (ratio)	700:1	Unit certification	CE, FCC, ROHS
Operating Temp (C)	0 - 50	Power certification	CE, FCC, ROHS, UL

\* Exact sizes may change due to further improvements.

## 15.6” DISPLAY

## MM156

Size diagonal (Inches)	15.6"	Unit size WxH (inches)	16.2 x 11.2
Active Area WxH (inches)	13.59 x 7.66	Surface Treatment	Anti-Glare, 3H
Resolution (pixels)	1920 x 1080	Shipping size WxHxD (inches)	14 x 12 x 6 (in box)
Viewing angle L/R/D/U	80/80/80/80	Shipping weight (Lbs)	6.75 (in box)
Brightness (cd/m2)	300	Mounting pattern (mm)	75x75
Contrast (ratio)	700:1	Unit certification	CE, FCC, ROHS
Operating Temp (F)	32 - 122	Power certification	CE, FCC, ROHS, UL

\* Exact sizes may change due to further improvements.



